



**PIE DIFFUSION**  
4 Rue des Maraichers  
78260 ACHERES  
Tel. 01.39.11.61.62  
Fax 01.39.11.72.00

## Cutting, stamping and bending machine Type C 043/E



### Specification:

- Dimensions: 600 x 480 x 450 mm
- Weight: approx. 45 kgs
- Connection: 230 V / 50 Hz / 200 W
- Bending part: horizontal and vertical bending
- Min. pitch: horizontal bending: 7,5 mm  
vertical bending: 2,5
- Max. pitch: horizontal bending: 50 mm  
vertical bending: 5 (7,5) mm
- Wire diameter: horizontal: from 0,4 to 1,3 mm  
vertical: up to 0,8 mm
- Components: taped
- Capacity: max. 8000 BE/h  
(directly adjustable)
- Option:
  - Manual supply for loose components
  - Display for cutting and pitch dimensions
  - Counter for preselection and number of pieces
  - Loading location for ammo-pack and reel
  - Safety switch-off for ammo-pack

### Function:

To make the insertion of axial wired components with short leads possible, the components leads have to be cut to the suitable length and bent to the required pitch and -if necessary- stamped.

Both suitable cutting length and required pitches can be adjusted by adjusting screws. After that the components can be processed. The set-up is shown on the scale of the each specific device.

Option: the adjustments can be checked by a digital display.

The stamping result for the leads depends on the used tool. These tools can be manufactured to meet customers requirements. The device can be re-set for the different tools.

The taped components can be processed automatically. The transport speed is directly adjustable.

The tool change for different bending dimensions takes about 5 minutes.

### Forms of the components:

